

6.6-12 Watt
Single Output Wall Mount Power Supply

Features:

- * Universal AC Input (90-264VAC / 47-63 Hz)
- * ErP Step 2 / CEC Level V Compliance
- * No load power Consumption less than 0.3 Watts
- * Small 2.44 x 1.06 x 1.81" Wall Mount Package
- * Plastic (UL 94V-0 Rated) Enclosure
- * Class II Safety Approvals (No Ground Required)
- * UL / cUL 60950-1 Safety Approvals
- * EN55022 class B, FCC PART 15 class B Emissions
- * 2 Year Warranty



Input Specifications:

Input Range	Universal VAC (90-264 VAC)
Input Frequency	47-63 Hz or DC
Inrush Current	less than 80A @ 230VAC (cold start)
Input Current	500mA@ 115 VAC max continuous
Input Reflected Ripple	FCC 68 part 15 Class B
Efficiency	68-79% minimum
Input Protection	Single Fused (1 Amp / 250 V)
Hold-up Time	15ms minimum (full load)
Leakage Current	<250µA maximum @ 240 VAC
Harmonics	EN61000-3-2 Class D

Output Specifications:

Adjustment Range	Fixed At Factory
Minimum Load	None
Regulation	±1% Line / ±5% Load
Ripple / Noise	1% pk-pk max (20MHz)
Transient Response	+/- 5% Deviation / < 1msec recovery
Set-Point Accuracy	±1%
Short Circuit Protection	Continuous
Over Load Protection	110-250%, hiccup mode
Over Voltage Protection	120-180% zener diode

Emissions Standards

FCC Part 15J, Part 2	Within Class B Limits
EN55022 / CISPR22	Within Class B Limits

Electromagnetic Compatibility:

Electrostatic Discharge	EN61000-4-2, ±4KV Contact / ±8KV Air Discharge
Radiated Susceptibility	EN61000-4-3, 26-1000MHz, 10V/M, 80% AM
EFT / Bursts	EN61000-4-4, ± 2KV
Surges	EN61000-4-5, ±2KV Line-Earth, ±1KV Line-Line
Conducted Immunity	EN61000-4-6, 0.15 - 800MHz, 10V, 80% AM
Voltage Dips	EN61000-4-11, 95% Dip & 10ms, 30% Dip & 500ms
Voltage Interruptions	EN61000-4-11, 95% Reduction, 5s
Radiated Emissions	FCC 68 part 15 Class B
Conducted Emissions	FCC 68 part 15 Class B
Harmonic Current	EN61000-3-2 Class D
Fluctuations & Flicker	EN61000-3-3

Environmental Specifications:

Operating Temp	0 ~40°C (De-Rate 5%/°C Rise up to 50°C)
Storage Temp	-20 ~ +85°C
Cooling	Convection Cooled
Temp Co-Efficient	0.4% per °C
Humidity	20-90%RH (non-condensing)
Vibration	0-200Hz, 2.5Grms, 30min /per axis (3axes)
Shock	20G Peak Acceleration
Reliability	50k hours MTBF (MIL-HDBK-217F)

International Safety Approvals

Qualified to Meet	UL/cUL60950-1 CE Mark (LVD)
-------------------	--------------------------------

EN55022 class B, FCC PART 15 class B Emissions

Model Number	Watts	Output	CEC Level	DC Cable	Efficiency
WRG10F-05AA	12.5W	5V/2.5A	4	AWG18x6FT	74%
WRG10F-120A	12W	12V/0.83A	5	AWG18x6FT	79%

Note:

- * Standard Output Connector is 5.5 x 2.1 x 11mm Barrel Jack (straight) with center positive.
- * All efficiency data are base on 115VAC and full load.
- * Consult your salesperson to request other cable / connector option

Mechanical Specifications:

Construction: Wall Mount

Weight: 0.35 lbs.

